

EL-852038I

ZKT_{ECO}

| BioEco Series | 2MP Motorized Lens Face Detection Eyeball IP Camera



- 1/2.9" 2MP CMOS sensor
- H.265 dual stream encoding
- High quality optical lens 3.35~10.05mm
- IR effective range 50m
- Built-in PoE
- Embedded face detection algorithm
- Support White/Black list alarm deployment
- Intelligent video analytic function supported
- Multiple web browsers supported
- Support P2P cloud remote viewing by Mobile Application/VMS
- Lightning protection up to 6KV
- Metal casing compliance with IP67 standard



System Overview

BioEco Series IP cameras are cost-efficient solution which powered by cutting-edge technology for crystal clear video monitoring. with embedded face detection algorithm, the cameras support White/Black list event alarm deployment in different scenarios. the cameras also support multiple industry-leading Intelligent video analytic functions, such as Face Detection, Line Crossing, Intrusion, Object Left/Lost, Counting, etc. for smart event alarms. P2P cloud function is built-in for every device which is more convenient and flexible for remote real-time viewing.

Technical Specifications

Functions

H.265

H.265 technology is an evolutionary optimization of traditional H.264, it includes a series of encoding strategy such as dynamic ROI, smart 2D&3D noise reduction, etc, for delivering high quality video, as well as greatly saving up to 70% bandwidth and storage.

Protection

With precise mechanical and rugged metal casing design, EZ series IP cameras could stand against water and dust with industrial IP67 rank.

Supports±10% input voltage tolerance, the cameras could work safely in extreme unstable power conditions.

With working temperature range -30°C to +60 °C, the cameras could be used in a variety of harsh outdoor environments.

Camera			
Model	EL-852038I	Flash/DDR	128Mb/512Mb
Image Sensor	1/2.9" CMOS	IR LED No.	2
Effective Pixels	1920*1080	IR Distance	50m
Min. Illumination	Color: 0.1Lux@F1.2 (AGC ON) B/W: 0.001Lux@F1.2 (AGC ON)	S/N Ratio	> 52dB
Lens			
Lens Type	Motorized	Aperture	F1.7~F3.0
Mount Type	Board-in	FOV	38°~101°
Focal Length	3.35mm-10.05mm	Optical Zoom	4X
Video			
Compression	H.265/h.264	WDR	DWDR
Resolution	1080P(1920×1080),1.3M(1280×960),720P(1280×720)	Day/Night	Support
Bitrate Control	CBR/VBR	White Balance	Support
Bitrate	H.265:1536Kbps-4Mbps H.264:1792Kbps-4Mbps	Defog	Support
Multi-Streaming	Main stream:1080P@25fps	Noise Reduction	2D/3D DNR
	Sub stream:Q720P@25fps	Mirror/Flip	Support
	Third stream:N/A	Corridor Mode	N/A
Motion Detection	Support	HLC	N/A
Digital Zoom	Support	BLC	Support
Audio Compression	G7.11u	ROI	4 areas
Privacy Mask	5 areas	Anti-flicker	Support

Technical Specifications

IVA			
Intelligent Video	Face Detection/Line Crossing/Intrusion/ Object Left/Lost/Counting/ Video Tampering		
Facial Recognition			
Face Templates	N/A	Face Quality Filtering	Support
Face Detected per Frame	30	Detection Area	User-defined
Detected Face Size	80x80~300x300 Pixels	Capture Response	≤1s
Network			
Protocol	TCP/IP,UDP,HTTP,DHCP,RTSP,NTP	Management Software(VMS)	AntarVis 2.0
Interoperability	ONVIF, SDK, API	Operation System	Windows
Max. Online Users	5	Mobile APP	AntarView Pro
Web Browser	IE/Firefox/Chrome/Safari	P2P Cloud Service	Support
Note: Video streaming is not available for Firefox/Chrome/Safari.			
Interface			
Ethernet	1 RJ-45 port (10/100Mbps)	Reset Button	N/A
Audio I/O	1/0	Micro-SD Slot	N/A
Alarm I/O	N/A	ANR	N/A
RS485	N/A	USB	N/A
General			
Power Supply	PoE (IEEE802.3af), DC 12V±10%	Working Temperature	-30°C ~+60°C
Power Consumption	<3W	Working Humidity	0%~90%
Ingress Protection	IP67	Net Weight	0.40 kg
Dimensions	Φ111.6*105mm	Gross Weight	0.64 kg

EL-852038I



| BioEco Series | 2MP Motorized Lens Face Detection Eyeball IP Camera

Order Information

Type	Model	Description
2MP Camera	EL-852038I	2MP Motorized Lens Face Detection Eyeball IP Camera

Dimensions

