

DBL522-01 | BioX Series

5MP Advanced Algorithm Face Detection Bullet IP camera



- 1/2.7" 5MP CMOS Sensor
- H.265 triple stream encoding
- 3.6mm high-quality optical lens
- 30m IR effective range
- Super 120dB WDR
- Intelligent video analytics available such as Face detection, Intrusion, Counting etc
- Multiple web browsers supported
- Lightning protection up to 4kV
- IP67 ingress rating
- Built-in PoE

System Overview

The BioX Series of Advanced Algorithm IP Cameras offer computer vision technology with edge-performing complex real-time intelligent functions.

It is capable of providing multiple industry-leading intelligent video analytic functions, such as Face Detection, Line Crossing, Intrusion, Counting, Rapid Movement, Queue Detection, etc.

The false alarm filter function could effectively filter out the leaves, shadow motions and only focus on main targets such as human and vehicle movement.

Meanwhile, the series benefits from the powerful 1 TOPS chipset and ISP optimization and performs excellently in weak/strong light comparison and foggy scenarios to deliver the promising crystal-clear images.

Functions

H.265

Extra H.265 encoding could save 50% bandwidth and storage capacity at least.

On-board Edge Storage Function

Support up to 256GB massive data storage on board when used as standalone devices.

Protection

The BioX series is rated IP67, which means it could stand against water and dust for a long time with its precise mechanical and durable materials.

With 10% of input voltage tolerance, the cameras could work safely under extreme or unstable power conditions.

With a working temperature range from -30°C to 55°C, the cameras could adapt to various harsh outdoor environments.

Technical Parameters

Camera

Model	DBL522-01	Flash / DDR	2GB / 4GB
Image Sensor	1/2.7" CMOS Sensor	IR LED No.	2
Effective Pixels	2560*1920	IR Distance	30m
Min. Illumination	Color: 0.005Lux (F1.6, AGC ON) B/W: 0.0005Lux (F1.6, AGC ON)	S/N Ratio	>52dB

Lens

Lens Type	Fixed	Aperture	F1.6
Mount Type	Board-in	FOV	79.2°
Focal Length	3.6mm	Optical Zoom	N/A

Video

Compression	H.265 / H.264	WDR	TWDR (120dB)
Resolution	2560 * 1920 / 2560 * 1440 / 2048 * 1536 / 1920 * 1080 / 1280 * 720 / 720 * 576 (PAL) / 720 * 480 (NTSC) / 352 * 288 (PAL) / 352 * 240 (NTSC)	Day / Night	Support
Bitrate Control	CBR / VBR	White Balance	Support
Bitrate	1080p - 5MP: 512Kbps - 16Mbps 720p: 384Kbps - 8Mbps D1: 256Kbps - 4Mbps CIF: 32Kbps - 1Mbps	Defog	Support
Multi-Streaming	Main Stream: 5MP@20fps	Noise Reduction	2D/3D DNR
	Sub Stream: 720p@25fps	Mirror/Flip	Support
	Third Stream: D1@25fps	Corridor Mode	Support
Motion Detection	Support	HLC	Support
Digital Zoom	Support	BLC	Support
Audio Compression	N/A	ROI	4 areas
Privacy Mask	12 areas	Anti-flicker	Support

IVA

Intelligent Video	FaceDetection / Line Crossing / Intrusion / Counting / Rapid Movement / Video Shelter / Scene change / VQD / Density Detection / Queue Detection
-------------------	---

Face Detection

Face Templates	N/A	Face Quality Filtering	Support
Face Detected per Frame	30	Detection Area	User-defined
Detected Face Size	50 x 50 Pixels	Capture Response	≤1s

Network

Protocol	TTCIP, UDP, IPv4, IPv6, DHCP, DHCPv6, DNS, ICMP, ICMPv6, IGMP, HTTPS, FTP, SFTP, RTP, RTSP, RTCP, SIP, ARP, SSL, NTP, SNMP(V1/V2/V3), 802.1x, QoS, DDNS, SMTP, PPPoE	Management Software (VMS)	ZKBioSecurity IVS ZKBioAccess IVS
Interoperability	ONVIF Profile S, SDK, API	Operation System	Windows
Max. Online Users	10	Web Browser	IE / Firefox / Chrome

Interface

Ethernet	1 RJ-45 port (10/100Mbps)	Reset Button	N/A
Audio I/O	N/A	Micro-SD Slot	Max 256GB
Alarm I/O	N/A	ANR	Support
RS485	N/A	USB	N/A

General

Power Supply	PoE (IEEE802.3af), DC 12V±10%	Working Temperature	-30°C to 55°C
Power Consumption	<5W	Working Humidity	5% to 95%
Ingress Protection	IP67	Net Weight	0.60kg
Dimensions (L*W*H)	210.2 * 108.6 * 91.4 (mm)	Gross Weight	0.86kg

Order Information

Camera	Model	Description
5MP Camera	DBL522-01	5MP Advanced Algorithm Face Detection Bullet IP camera

Dimensions (mm)

